

# MIL-RAM TECHNOLOGY

no false alarms

Since 1990

ISO 9001:2008 Registered

Tel: 510-656-2001 • Toll-Free: 888-464-5726 • Email: sls@mil-ram.com • Web: mil-ram.com



## Model TA-2100 *smarter* Catalytic LEL Combustible Gas Detector

### ➤ Features

**no false alarms** catalytic bead sensor technology

Self-Calibration adjusts monthly based on sensor life curve

Auto-Gas Calibration, non-intrusive, hands-free, magnetic switches

Not affected by temperature -40°C to +75°C, stable by design

LCD display - 12 characters x 2 lines - provides user interface with magnetic switches - no dip switches - LED alarm indicators

Offsite sensor calibration with memory chip embedded in sensor

Peak Value, 15-min. TWA, Remaining Sensor Life, Replace Sensor indication and number of days since last gas calibration

Optional Relay Module; low, mid, high and fault conditions

Optional RS-485 Modbus RTU Network interface

Available suitable for use in **SIL 2** environments / Advanced diagnostics

Part No. 01-2620

#### Options

- Modbus RTU
- Relay Module
- Sensor Cable
- Sample Pump
- Duct Mount Kit
- Dust Guard
- Splash Guard
- Wireless Module
- 110/220 VAC
- Calibration Kits
- 316 SS Enclosure

### ➤ Specifications

Detection Principle:	Catalytic bead LEL combustible
Detection Method:	Diffusion or Sample Drawing
Detection Range:	0 - 100% LEL (lower explosive limit)
Calibration Method:	Non-intrusive, magnetic tool
Operating Voltage:	12 - 30 VDC, 24 VDC nominal
Power Requirements:	1.82 W @ 24 VDC
Electrical Connections:	Power (24 VDC) and Signal (4-20mA)
Cable Requirements:	3 or 4 wires, shielded
Optional Connections:	RS-485 Half-duplex (Modbus RTU)
Resolution:	1% LEL minimum detection level
Zero Drift:	less than 1% of full-scale
Temperature Range:	-40°C to +75°C
Humidity Range:	0 - 99% RH, non-condensing
Response Time:	<10 sec. to 50% of full-scale
Recovery Time:	<30 sec. to 90% recovery
Sensor Service Life:	>3 years typical; normal conditions
Electronic Enclosure:	Ex-Proof, alum. or 316 SS, Nema 4x
Certifications:	CSA, Class I, Div. 1, Groups B,C,D

### ➤ Applications

Oil & Gas Exploration

Chemical Processing

Oil Refining

Steel Mills

Mud Logging

Laboratories

Natural Gas Distribution

More

Specifications subject to change without notice due to continued program of product innovation.

Toxic • LEL Combustible • Oxygen • VOCs • Hydrides • Hydrocarbons  
Gas Detection **no false alarms** Fire Detection

Tel: 510-656-2001 • Fax: 510-656-2004 • Email: sls@mil-ram.com • Fremont, CA